



# Fact Sheet

## U.S. Air Force Fact Sheet C-17 GLOBEMASTER III

### **Mission**

The C-17 Globemaster III is the newest, most flexible cargo aircraft to enter the airlift force. The C-17 is capable of rapid strategic delivery of troops and all types of cargo to main operating bases or directly to forward bases in the deployment area. The aircraft can perform tactical airlift and airdrop missions and can transport litters and ambulatory patients during aeromedical evacuations when required. The inherent flexibility and performance of the C-17 force improve the ability of the total airlift system to fulfill the worldwide air mobility requirements of the United States.



The ultimate measure of airlift effectiveness is the ability to rapidly project and sustain an effective combat force close to a potential battle area. Threats to U.S. interests have changed in recent years, and the size and weight of U.S.-mechanized firepower and equipment have grown in response to improved capabilities of potential adversaries. This trend has significantly increased air mobility requirements, particularly in the area of large or heavy outsize cargo. As a result, newer and more flexible airlift aircraft are needed to meet potential armed contingencies, peacekeeping or humanitarian missions worldwide. The C-17 is capable of meeting today's demanding airlift missions.

### **Features**

Reliability and maintainability are two outstanding benefits of the C-17 system. Current operational requirements impose demanding reliability and maintainability. These requirements include an aircraft mission completion success probability rate of 92 percent, only 20 aircraft maintenance man-hours per flying hour, and full and partial mission availability rates of 74.7 and 82.5 percent, respectively. The Boeing warranty assures these figures will be met.

The C-17 measures 174 feet long (53 meters) with a wingspan of 169 feet, 10 inches (51.75 meters). The aircraft is powered by four, fully reversible, Federal Aviation Administration-certified F117-PW-100 engines (the military designation for the commercial Pratt & Whitney PW2040), currently used on the Boeing 757. Each engine is rated at 40,440 pounds of thrust. The thrust reversers direct the flow of air upward and forward to avoid ingestion of dust and debris. Maximum use has been made of commercial off-the-shelf equipment, including Air Force-standardized avionics.

The aircraft is operated by a crew of three (pilot, co-pilot and loadmaster), reducing manpower requirements, risk exposure and long-term operating costs. Cargo is loaded onto the C-17 through a large aft door that accommodates military vehicles and palletized cargo. The C-17 can carry virtually all of the Army's air-transportable equipment.

Maximum payload capacity of the C-17 is 170,900 pounds (77,519 kilograms), and its maximum

gross takeoff weight is 585,000 pounds (265,352 kilograms). With a payload of 169,000 pounds (76,657 kilograms) and an initial cruise altitude of 28,000 feet (8,534 meters), the C-17 has an unrefueled range of approximately 2,400 nautical miles. Its cruise speed is approximately 450 knots (.74 Mach). The C-17 is designed to airdrop 102 paratroopers and equipment.

The design of the aircraft allows it to operate through small, austere airfields. The C-17 can take off and land on runways as short as 3,500 feet (1,064 meters) and only 90 feet wide (27.4 meters). Even on such narrow runways, the C-17 can turn around using a three-point star turn and its backing capability.

## **Background**

The C-17 made its maiden flight on Sept. 15, 1991, and the first production model was delivered to Charleston Air Force Base, now known as Joint Base Charleston, S.C., on June 14, 1993. The first squadron of C-17s, the 17th Airlift Squadron, was declared operationally ready Jan. 17, 1995. The Air Force originally programmed to buy 120 C-17s. Current budget plans increased the total number to 223 aircraft.

The C-17 is operated by Air Mobility Command at Travis AFB, Calif.; Dover AFB, Del.; Joint Base Lewis-McChord, Wash.; Joint Base Charleston, S.C., and Joint Base McGuire-Dix-Lakehurst, N.J.

The Air National Guard flies C-17s from the 172d Airlift Wing, Jackson, Miss., and the 105th Airlift Wing, Stewart ANGB, N.Y. Additionally, Air Force Materiel Command operates two C-17s at Edwards AFB, Calif., and Pacific Air Forces operates aircraft at Joint Base Elmendorf-Richardson, Alaska, and Joint Base Pearl Harbor-Hickam, Hawaii.

The Air Force Reserve Command operates aircraft at March Air Reserve Base, Calif., and Wright Patterson AFB, Ohio. Air Education and Training Command has 17 aircraft at Altus AFB, Okla.

## **General Characteristics**

**Primary Function:** Cargo and troop transport

**Prime Contractor:** Boeing Company

**Power Plant:** Four Pratt & Whitney F117-PW-100 turbofan engines

**Thrust:** 40,440 pounds, each engine

**Wingspan:** 169 feet 10 inches (to winglet tips) (51.75 meters)

**Length:** 174 feet (53 meters)

**Height:** 55 feet 1 inch (16.79 meters)

Cargo Compartment: length, 88 feet (26.82 meters); width, 18 feet (5.48 meters); height, 12 feet 4 inches (3.76 meters)

**Speed:** 450 knots at 28,000 feet (8,534 meters) (Mach .74)

Service Ceiling: 45,000 feet at cruising speed (13,716 meters)

**Range:** Global with in-flight refueling

**Crew:** Three (two pilots and one loadmaster)

**Aeromedical Evacuation Crew:** A basic crew of five (two flight nurses and three medical technicians) is added for aeromedical evacuation missions. Medical crew may be altered as required by the needs of patients

**Maximum Peacetime Takeoff Weight:** 585,000 pounds (265,352 kilograms)

**Load:** 102 troops/paratroops; 36 litter and 54 ambulatory patients and attendants; 170,900 pounds (77,519 kilograms) of cargo (18 pallet positions)

**Unit Cost:** \$202.3 million (fiscal 1998 constant dollars)

Date Deployed: June 1993

**Inventory:** Active duty, 187; Air National Guard, 12; Air Force Reserve, 14

(Current as of May 2014)